



Tenax India Stone Products Private Limited, 49-a2 Canara Bank Road next to Bharat Tissus, Bommasandra Industrial Area, Bangalore – 99 INDIA,
Ph: +91 80 41100875, Fax: +91 80 41100874, E-mail: sales@tenaxindia.in

TECHNICAL DATA SHEET Re-issued: 06/09/2018 rev.00

Pag.1/2

EPOXY RESIN 943

DESCRIPTION

PRODUCT: Liquid Epoxy resin

DESCRIPTION: Epoxy resin for resining and netting natural stone, medium viscosity, good reactivity at low temperature, medium hardness.

INSTRUCTIONS OF USE

The product must be kept on the original cans. Avoid the contact with metals made of copper, brass or similar metals which may rust. Avoid the use of plastic made of PVC, do use only plastic liquid corrosive resistance. Take out from the two containers the required amounts in weight of the two components. During the mixing use clean tools. Ensure that the stone to be treated with the resin is completely dry and clean. In case of automatic dosing pumps, we suggest to verify the ratio every day. To clean the tools, we suggest to use aromatic and light solvent, like acetone and butyl acetate.

Use safety gloves and safety glasses during the work (see the safety data sheet). Close the cans after the usage, avoid the long exposure on the air.

SALES SPECIFICATION

Viscosità/Viscosity :	850 - 1250 cps -25°C	ASTM D2196
Aspetto/Aspect:	Liquido trasparente-opaco / Clear hazy-liquid	
Shelf life:	24 months at 18-25°C (1)	

(1) When it is stored in original tightly closed container, keep away from source of heat, rays sun, humidity and rain.

The information included in the present technical data sheet are based on tests carried on in our laboratory and are correct, based on our experience. The present data can be changed without notice and shall not be considered legally relevant. It is under the responsibility of the customer to verify the suitability of the product before use. It is obligation of the customer to verify that the use of the product is done according to laws, legislation, patents of the customer's country.



Tenax India Stone Products Private Limited, 49-a2 Canara Bank Road next to Bharat Tissus, Bommasandra Industrial Area, Bangalore – 99 INDIA,
Ph: +91 80 41100875, Fax: +91 80 41100874, E-mail: sales@tenaxindia.in

TECHNICAL DATA SHEET Re-issued: 06/09/2018 rev.00

Pag.2/2

VERSION AVAILABLE :

Versione AX :

Available

Versione MX :

Available

Versione PH :

Available

INCOMPATIBLE EPOXY HARDENERS : BB28H, BM33H, BB36H.

SAFETY RULES

Resin is chemical product, please read the safety data sheet MSDS before usage and the rules written on the label on the tins/drums.

STORAGE CONDITION

*Keep the resin in original tightly closed containers, in a dry place far away from source of heat and rays sun.
Avoid freezing condition.*

The information included in the present technical data sheet are based on tests carried on in our laboratory and are correct, based on our experience. The present data can be changed without notice and shall not be considered legally relevant. It is under the responsibility of the customer to verify the suitability of the product before use. It is obligation of the customer to verify that the use of the product is done according to laws, legislation, patents of the customer's country.