

# Marvel Shine Pro

Natural-effect polishing powder for delicate marble surfaces

## DESCRIPTION

Marvel Shine Pro is a high-performance polishing powder with a formula that is completely wax free and low in acid content. Marvel Shine Pro can be used to polish delicate marble surfaces and all of those materials that are particularly sensitive to acids and which otherwise are at risk of developing an “orange peel-effect” finish following the use of aggressive products. Marvel Shine Pro reacts with the material to which it is applied, boosting shine. At the same time, it gives treated surfaces a good, long-lasting level of resistance to dirt and foot traffic.



## INSTRUCTIONS FOR USE

The product is suitable to be used both indoors and outdoors on marble, limestone; travertine; marble-cement agglomerates; marble-resin agglomerates.

## TECHNICAL DATA

FORMULA Powder

COLOR: White

SCENT: Slight Scent

pH: 1,5 ± 0,5

## APPLICATION EQUIPMENT

Single disk machine, Hand polisher .

## APPLICATION

- Carefully clean the surface, making sure to remove any dust or dirt present.
- We recommend proceeding to apply the product in stages, covering surfaces approximately 2m<sup>2</sup> at a time.
- Pour 2-3 spoons of product onto the surface to be treated.

- Add a sufficient amount of water to the product to create a creamy/fluid paste that is easy to distribute. As a rough guide, each spoonful of product requires around 2 spoons of water.
- As soon as the water has been added to the powder, proceed to apply it to the surface using the single disc machine, fitted with a white pad, and set to 150 - 200 r.p.m. Continue with the single disc machine, taking care to cover the whole surface area evenly with the powder and water paste. Try to pass over each section of the floor the same number of times.
- During the application process, the mix must maintain its creamy consistency, and therefore, if it should become too dry, gradually add a little water.
- Continue to buff with the single disc machine until the surface has reached its maximum shine. The shine results are easy to check during application by removing a small area of product using a squeegee mop or similar and checking the level of shine achieved.
- Once the required shine has been achieved, vacuum or remove any residues from the surface. Pass on to the area of the next surface.

## INSTRUCTIONS AND GUIDELINES

- Do not allow the product to dry during the application process. Frequently check consistency and add water as needed to return the product to its fluid/creamy state.
- Never apply the product to a wet surface
- Do not apply the product to overly heated surfaces.
- Apply the product to surfaces with a temperature of between +5 and +40°C
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

## COVERAGE

For surface polishing: 40/50 m<sup>2</sup>/kg

For surface maintenance: 50/100 m<sup>2</sup>/kg

## STORAGE

Keep the container closed in a cool and dry place.

## SHELF LIFE

48 months in the original sealed packaging, stored in a cool and dry place.