

OVERVIEW & BENEFITS:

Marvel Shine Classic is a high performance Beige color polishing powder designed specifically for marble and other acid sensitive surfaces. Its advanced, completely wax free formula contains a low level of acidity, making it safe for marble. By reacting with the stone, Marvel Shine Classic enhances the natural shine while providing a durable finish that resists dirt and heavy foot traffic. This balance of gentle care and long lasting protection makes it an ideal solution for maintaining the beauty and integrity of premium stone surfaces.



KEY FEATURES:



Low-Acid Formula

Safe for sensitive stones like marble and limestone.



Natural Shine

Enhances the stone's inherent beauty.



Versatile Use

Suitable for marble, travertine, and Natural stone.



Wax-Free Composition

Leaves no residue or artificial gloss.



Durable Finish

Provides resistance to dirt and wear



APPLICATION PROCESS:

Surface Preparation

- Clean the surface thoroughly to remove dust, dirt, and residues.
- Ensure the surface is dry and not overheated.
- Do not apply to wet or recently grouted surfaces.

Application

- Apply in sections of approx. 2 m².
- Pour 2–3 spoons of Marvel Shine Classic powder onto the surface.
- Add 2 spoons of water per spoon of powder to form a creamy paste.
- Use a single-disc machine (150–200 RPM) with a white pad to polish.
- Maintain a creamy consistency by adding water as needed. Continue
- polishing until the desired shine is achieved.

Finishing

- Remove residues using a vacuum or mop.
- Proceed to the next section and repeat the process.

TECHNICAL DATA

Property	Value
Formula	Powder
Color	Yellow (Biege)
Scent	Slight 1.5 ± 0.5 Single-disc
pH	machine, hand polisher +5°C to
Application Equipment	+40°C
Application Temp.	

COVERAGE:

Material Type	Coverage/Kg
Coverage (Polishing)	400–500 sq .ft
Coverage (Maintenance)	500–1000 s

AVAILABLE SKU:

1kg and 5 kg

RECOMMENDED USES:



Marble & Limestone

Ideal for delicate, acid-sensitive surfaces.



Travertine

Enhances natural shine without damage.



Indoor & Outdoor Applications

Versatile for various environments.

DO'S AND DON'TS:

Do's	Don'ts
Clean the surface thoroughly before use	Do not use on non-calcareous stones (e.g., granite)
Mix properly with water to form a creamy paste	Avoid aggressive pads or brushes that can scratch
Use a single-disc machine with a white pad	Do not apply on dirty or wet surfaces without cleaning
Work in small sections for even polishing	Do not mix with other chemicals or powders
Rinse and dry the surface after polishing	Avoid excessive product use
Store in a cool, dry place	Do not leave slurry on the surface for too long

STORAGE AND SHELF LIFE:

Store in a cool, dry place away from direct sunlight and extreme temperatures. Keep containers tightly sealed. Shelf life is 48 months in original, unopened packaging under recommended storage conditions.



Pidilite Industries Limited, Ramkrishna Mandir Road, P. O. Box No. 17411, Andheri (E), Mumbai - 400 059

DISCLAIMER: The information provided is for guidance only and does not constitute a warranty of any kind. Tenax is not liable for any damage resulting from the use or misuse of the product. Product suitability should be verified for specific applications, and users must ensure they are referring to the latest version of the data sheet. Specifications may change without notice.