

## OVERVIEW & BENEFITS:

Tenax Proseal is a solvent-based hydro-oleophobic impregnator sealer designed to protect natural stone, quartz agglomerates, and porous marble. It provides long-lasting protection against water, oil, and stains while maintaining the natural look of the material. Its deep penetration and weather resistance make it ideal for both indoor and outdoor applications, including large surfaces.



## KEY FEATURES:



### Natural effect

Does not alter color or create surface films.



### Water & oil repellency

Protects against stains and moisture.



### Deep penetration

Bonds to microporosities for durable protection.



### Weather-resistant

Suitable for outdoor use.



### Easy application

Ideal for large areas and multiple finishes (polished, honed, brushed).

## APPLICATION PROCESS:

### Surface Preparation

- Clean the surface thoroughly to remove dust, grease, and residues.
- Ensure the surface is completely dry before application.
- Avoid direct sunlight during application.

### Application

- Apply evenly using a brush, roller, sponge, or spray gun.
- Avoid pooling or excessive application, as a thin and uniform coat ensures the best absorption.
- Apply multiple coat to enhance durability.
- Work in small sections to ensure uniform coverage.  
After a few minutes, wipe off excess product with a clean cloth to prevent sticky films.

### Curing & Finishing

- Do not step on treated surfaces for 4–6 hours.
- Full protection achieved after 24 hours.
- Ensure proper air circulation to speed up drying and improve absorption into the material.

## TECHNICAL DATA

| Property        | Value                    |
|-----------------|--------------------------|
| Appearance      | Opalescent liquid        |
| Color           | Colorless                |
| Density @ 25°C  | ~0.820 g/cm <sup>3</sup> |
| Base            | Solvent-based            |
| Drying Time     | 4–6 hours                |
| Full Protection | 24 hours                 |

## COVERAGE:

| Material Type               | Coverage/L     |
|-----------------------------|----------------|
| Surfaces with Low Porosity  | 300–400 sq .ft |
| Surfaces with High Porosity | 200–300 sq. ft |

## AVAILABLE SKU:

1L and 250 ml

## RECOMMENDED USES:



### Marble & Granite

Flooring, facades.



### Quartz Agglomerates

Ideal for mixed silicate-carbonate surfaces.



### Porous Surface

Suitable for honed, sandblasted, and brushed finishes.

## DO'S AND DON'TS:

| Do's   | Don'ts  |
|--|---|
| Apply only to clean, dry surfaces to ensure even penetration and finish    | Do not apply to wet, dusty, or oily surfaces—it can cause uneven coverage |
| Test on an inconspicuous area first to confirm compatibility               | Avoid over-application—excess can leave a sticky or glossy film           |
| Apply evenly using a brush, sponge, cloth, roller, or low-pressure sprayer | Do not leave excess on the surface—buff off after a few minutes           |
| Buff off excess after a few minutes to prevent film formation              | Avoid direct sunlight exposure during application                         |
| Repeat application 10–15 minutes later for deeper protection               | Don't walk on newly treated floors for at least 24 hours                  |
| Allow 24 hours drying time before use to achieve stain resistance          | Do not leave the container open, seal it tightly after use.               |

## STORAGE AND SHELF LIFE:

Store in a cool, dry place away from direct sunlight and extreme temperatures. Keep containers tightly sealed. Shelf life is 24 months in original, unopened packaging under recommended storage conditions.



**Pidilite Industries Limited**, Ramkrishna Mandir Road, P. O. Box No. 17411, Andheri (E), Mumbai - 400 059

DISCLAIMER: The information provided is for guidance only and does not constitute a warranty of any kind. Tenax is not liable for any damage resulting from the use or misuse of the product. Product suitability should be verified for specific applications, and users must ensure they are referring to the latest version of the data sheet. Specifications may change without notice.